

NV-MPPT-20A

Description

Specifications

PV Solar Charge Controller MPPT design

- 1,1 year warranty
- 2, save 20%-30% solar panel
- 3,professional manufacture

PV Solar Charge Controller MPPT design Solar Controller is a solar charge controller with Maximum Power Point Tracking. It is specially designed to work with all established module technologies and is optimized for solar systems with module voltages higher than the battery voltage. The Solarix MPPT is especially qualified in combination with grid tied solar modules. The advanced MPP-tracking algorithm from Steca assures that the maximum available power of the solar generator is charged to the batteries. TheFangpusun-MPPT with latest technology ensures full performance in all conditions, a professional battery care combined with modern design and excellent protection.

Product features

Maximum Power Point Tracker (MPP tracker)

Voltage and current regulation

PWM control

Current compensated load disconnection

Automatic load reconnection

Temperature compensation

Monthly maintenance charge

Electronic protection functions

Overcharge protection

Deep discharge protection

Reverse polarity protection of load, module and battery

Reverse polarity protection by internal fuse

Automatic electronic fuse

Short circuit protection

Overvoltage protection at module input

Open circuit protection without battery

Reverse current protection at night

Overtemperature and overload protection

Battery overvoltage shutdown

Displays

Multifunction LED display

Multi-coloured LED

5 LEDs show operating states

- for operation, state of charge, fault messages

Options

Night light function pre-set in the factory or adjustable via Steca PA RC 100 Parameterisation of function values via Steca PA RC 100

Certificates

Compliant with European Standards (CE)

ROHS compliant

Made in china

Parameter

- aramotor		
	MPPT Solar Charge Controll	er
Model	MPPT-20	
Max.Charge Current	20A	
System Voltage	12V	24V
Max Solar Panel Voltage	25V	50V
Panel Voltage Tracking Range	12-25V	24-50V
Full Charge Cut	14V	28V
Charging Mode	Maximum Power Point Tracking (MPPT)	
Temp.Compensation	NO	
Dimension	18.8×12×5. 5cm(L×W×H)	
N.W./unit	0.65kg	
QTY/Ctn	20Pcs	
Packing	Gift box	
Carton Size / Weight	45×29×36cm , 18Kgs	
Warranty	12 Months	

Display

